

EASY LAB



TECHNICAL DATASHEET

STAIN REMOVING PASTE **TERRA COTTA - CEMENT - STONE - MARBLE - SLATE** **PAVING STONE - WOOD**

0900

ELIMINATES THE STANES OF OIL AND FAT ON ALL POROUS SURFACES.

APPLICATION

The support should not be varnished. A layer of 3 to 4 mm is applied with a spatula well by taking care to cover the stain and a large area around it to avoid making a halo. Drying should take about 12 hours and then remove the remaining powder. Repeat the operation if necessary.

ATTENTION

All surfaces can have a spot of "clean" stain which requires repeating the finishing treatment. Tannic oak, walnut, teak, exotic woods.... You can have a stain of tannin which can be eliminated with our thinner 0803.

Always repackage it in a smaller packaging adapted to the remaining amount

PACKAGING: 500 ml - 11 – 5 l – 30 l.

Security:



Please read the security instructions carefully
work in a well aired room
wear rubber gloves
keep out of reach of children

This information is given here in good faith but does not involve our responsibility.

LES BONS PRODUITS St ANTOINE - ANCIENNE PROVENCE - EUROWOOD LASURE

21 rue André Chénier 69120 Vaulx en Velin - France

Tel. 33 (0) 4 72 35 16 27 - Fax. 33 (0) 4 78 54 53 71 - E-Mail : easylab@easylabfinish.com

Internet : www.easylabfinish.com - RCS LYON B 349 783 712 00012 - NAF : 245 C