



TECHNICAL DATA SHEET

PROTEC WOOD

Matt finish aqueous wax oil

ANTI-UV EXTERNAL PROTECTION FOR WOODEN BUILDINGS

0271

Water repellent and ANTI UV treatment for external woodwork to protect weatherboarding, beams, safety rails and all woodwork. Does not change colour after ageing by oxidation.

PREPARATION

For renovation work, the wood must be free of all surface treatments. We recommend that you use **abrasive blasting or sanding** before applying any new product.

APPLICATION

On new or fully stripped wood apply two coats wet on wet. A second coat on a dry first coat will not adhere or stretch.

Apply by brush or spray (HVLP or AIRLESS) on all types of softwood.

- **DO NOT APPLY IN DIRECT SUNLIGHT**
- **APPLICATION TEMPERATURE: +5°C TO +30°C**

- This product can be coloured using **0272** bases. A broad range of possible colours is available.

FINISH

- ✚ **TOOL CLEANING:** Use water for tool cleaning.
- ✚ **COVERAGE:** 8 to 10 m² per litre (depending on absorbency of wood).
- ✚ **PACK SIZES:** 1L – 5 L – 30L and more.

SAFETY

- ✚ It is indispensable to wear rubber gloves
- ✚ Do not swallow
- ✚ Keep out of the reach of children

This information is given here in good faith but does not involve our responsibility.

LES BONS PRODUITS St ANTOINE - ANCIENNE PROVENCE - EUROWOOD LASURE

21, rue André Chénier 69120 Vaulx en Velin (Grand Lyon) - France

Tel. 33 (0) 4 72 35 16 27 - Fax. 33 (0) 4 78 54 53 71 - E-Mail: easylab@easylabfinish.com

Internet: www.easylabfinish.com - RCS LYON B 39 783 712 00046 - NAF: 245 C