



DATA SHEET

PROTEC WOOD

Matt finish aqueous wax oil

INTERIOR PROTECTION FOR WOODEN BUILDINGS 0273

Water repellent treatment for interior use to protect paneling, beams, safety rails and all woodwork. Does not change colour after ageing by oxidation.

PREPARATION

For renovation work, the wood must be free of all surface treatments. We recommend that you use **abrasive blasting or sanding** before applying any new product.

APPLICATION

On new or fully stripped wood apply one or two coats. Apply a second coat before the first coat dries. A second coat on a dry first coat will not adhere or stretch.

Apply by brush or spray (HVLP or AIRLESS) on all types of softwood.

- **DO NOT APPLY IN DIRECT SUNLIGHT**
- **APPLICATION TEMPERATURE +5°C TO +30°C**

This product can be coloured using 0272 bases. A broad range of pastel shades is available.

STIR WELL BEFORE USE

FINISH

- ✚ TOOL CLEANING: Use water for cleaning tools
- ✚ COVERAGE: 8 to 10 m² per litre (*depending on absorbency*).
- ✚ PACK SIZES: 1L – 5 L – 30L and more.

- ✚ Cleaning of tools: with water
- ✚ Quantities : 8 – 10 m² per liter depending on how porous the wood is
- ✚ Packaging: 1 liter, 5 liters, 30 liters and more.

Security measures

- ✚ It is indispensable to wear rubber gloves
- ✚ Do not swallow
- ✚ Keep out of the reach of children

This information is given here in good faith but does not involve our responsibility.

LES BONS PRODUITS St ANTOINE - ANCIENNE PROVENCE - EUROWOOD LASURE

21, rue André Chénier 69120 Vaulx en Velin (Grand Lyon) - France

Tel. 33 (0) 4 72 35 16 27 - Fax. 33 (0) 4 78 54 53 71 - E-Mail: easylab@easylabfinish.com

Internet: www.easylabfinish.com - RCS LYON B 39 783 712 00046 - NAF: 245 C