



DATA SHEET

TREATMENT POROUS COOKED LANDS INSIDE WATERPROOFING - OLEOFUGEANT WARM COLORS NOT FOLMOGENE 0534

This treatment protects terra-cottas of the marks of oil, fat, water. It leaves no visible movie.

APPLICATION

Do not use unless 15 °, on a ground warm or exposed to the sun. It applies in 2 or 3 coats to a new or ancient clean and dry ground, containing no track of the other treatment what would entail a bad penetration and a bad drying of the product. When terra-cottas are averagely porous and when the product does not penetrate very well we can dilute it with the active thinner 0435 which will allow to settle the viscosity without modifying the efficiency of the treatment 0534.

- ❖ **On a new ground:** after drying prepare the ground by eliminating the rashes of cement with our scouring agent 0820 (see FT). When the ground was rinsed well and when it is very dry to apply by means of a brush, of a roller or of a sponge the treatment 0534 in plentiful and regular crossed coats(layers). Watch in over one maid distribution and that there is no surplus.

Drying 4 at 8 am between every coat.

- ❖ **On a ancient ground:** he must be cleared of any preliminary treatment, use our high-powered cleaner 0901 (see FT). When the ground is ready and very dry to apply the treatment 0534 to see § the precedent.
- ❖ **FINISH :** After a drying of 72 am or more, we can apply a finish which will give a satiny aspect with our palm emulsion wax 0722 or a matchless shine with our wax to skate terra-cottas 0007. (See FT)

- ⇒ Cleaning of brushes: in the White spirit.
- ⇒ Coverage : 8 - 10 m2 in the liter according to the porosity of the support.
- ⇒ Packing: 1L- 5L – 30L

Safety Warning :

- ⚠ Read attentively the label of safety warning
- ⚠ Work in a well ventilated room
- ⚠ Do not swallow
- ⚠ Do not leave within the reach of the children

Honest given information but not engaging our responsibility