

EASY LAB



TECHNICAL DATASHEET

PROTECTION OIL

FOR FERROUS METALS FINISH AFTER TREATMENT WITH BLUING-AGENT

0860

This protective oil polymerizable satin enhances the colors and protects against rust (contains an inhibitor). It does not look form a coat.

APPLICATION

Ready for use. After treating the metal with cold-bluing agent 0805 or other, rinse thoroughly with water. When the room is dry, apply using a brush Oil Protection 0860 and allow to dry 2-4 hours at a temperature of 18 ° to 20 ° or more.

QUANTITIES :

15-18 m² /liter

SECURITY :

- ✚ Please read the security instructions carefully,
- ✚ work in a well aired room,
- ✚ wear rubber gloves,
- ✚ keep out of reach of children.

This information is given here in good faith but does not involve our responsibility.

LES BONS PRODUITS St ANTOINE - ANCIENNE PROVENCE - EUROWOOD LASURE

21 rue André Chénier 69120 Vaulx en Velin - France

Tel. 33 (0) 4 72 35 16 27 - Fax. 33 (0) 4 78 54 53 71 - E-Mail : easylab@easylabfinish.com

Internet : <http://www.easylabfinish.com/> - RCS LYON B 349 783 712 00046 - NAF : 245 C